



FREEHUB COMPATIBILITY

Freehub Body Type	Speed Compatibility	Notes on Compatibility
Coaster	Single speed	Splined cog, held in place by a snap ring. Also used on internal gear hubs.
Freewheel	5–8 speed and single speed	Requires 1.37" x 24TPI threaded freewheels
Fixed/Freewheel	Single speed	One side of the hub takes a track cog and lockring. The other side takes a 1.37" x 24TPI threaded freewheel.
BMX Freewheel	Single speed	Requires M30 threaded freewheels
BMX Cassette	Single speed	Requires BMX-specific cassettes
Campagnolo	9–12 speed	Requires Campy-specific cassettes
Shimano 7	7-speed	Requires 7-speed-specific cassettes
Shimano HG	MTB/Touring: 8–12 speed Road: 8–10 speed, some 11-speed cassettes	As of April 2019, the only 11-speed road cassettes that fit on this type of freehub body are Shimano's 11-34 CS-HG700-11 and CS-HG800-11
Shimano HG 11	MTB/Touring: 8–12 speed Road: 8–11 speed	A 1.85mm spacer is required for all 8–10 speed cassettes, for MTB 11- and 12-speed cassettes and also for Shimano's 11-speed 11–34 road cassettes
Shimano Micro Spline	11–12 speed	XTR M9100 cassettes only. Not retro-compatible with previous spline pattern.
SRAM XD	11–12 speed	All SRAM XD-compatible cassettes, from GX/GX Eagle to XX1/XX1 Eagle & Eagle AXS
SRAM XDR	11–12 speed	Mandatory for AXS Road cassettes. A 1.85mm spacer is required to for all other XD-compatible cassettes